

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 649 644 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
31.05.2000 Bulletin 2000/22

(51) Int. Cl.⁷: **A61F 13/15**

(21) Application number: **94115024.5**

(22) Date of filing: **23.09.1994**

(54) Stabilized absorbent core and products made therefrom

Stabilisierter absorbierender Kern und daraus hergestellte Produkte

Noyau absorbant stabilisé et produits préparés de cela

(84) Designated Contracting States:
AT BE CH DE ES FR GB GR IE IT LI NL PT SE
Designated Extension States:
SI

(30) Priority: **24.09.1993 US 126936**

(43) Date of publication of application:
26.04.1995 Bulletin 1995/17

(73) Proprietor: **McNEIL-PPC, INC.**
Milltown New Jersey 08850 (US)

(72) Inventors:
• **Fung, Paul Y.**
South River, NJ 08882 (US)

• **Galloway, Robert A.**
Lawrenceville, NJ 08648 (US)

(74) Representative:
Groening, Hans Wilhelm, Dipl.-Ing. et al
BOEHMERT & BOEHMERT
Franz-Joseph-Strasse 38
80801 München (DE)

(56) References cited:
EP-A- 0 376 761 **US-A- 3 963 029**
US-A- 4 560 379 **US-A- 4 576 596**
US-A- 5 088 993

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 649 644 B1

Description

[0001] This invention relates to an absorbent product for use in a wearer's garment and to an absorbent core for use in an absorbent product suitable for placement in a wearer's garment in accordance with the preamble of claims 1, 11 and 12. The preamble of said claim is based on EP-A-0 376 761.

[0002] EP 0 376 761 is related to an article for feminine hygiene comprising absorbent material consisting of fluff being impregnated with a mixture formed from a bacteriostatic and fungistatic agent and a deodorant in a non-volatile hydrophilic solvent adhering to the cellulosic fibers.

[0003] US-A-4 576 596 discloses a sanitary napkin having an absorbent layer folded back along itself to form a top layer and bottom folded layer which abut each other near the central portion of the napkin. A thin extra-absorbent layer is positioned within the fold and the folding end position of the absorbent layer. A further fold is provided by an additional layer. The known napkin can have four absorbent layers and a raised center area. A further embodiment of this known napkin provides an open central area with a single fold with a folded portion being positioned on the upper portion of the napkin.

[0004] Despite the many advances that have been made in the design of absorbent products such as diapers, incontinent products and sanitary napkins, there is a constant need for improved products that will offer the user greater security. Ways to enhance the absorbent capacity of such products have been found and widely utilized, for example, the inclusion of superabsorbent materials in product design. However, despite increased absorbent capacity, tests show that a surprisingly high proportion of such products still fail, i.e., the wearer experiences leakage and staining. In large part, such failure is due to the stress imposed upon the product during use. A sanitary napkin, for example, is subjected to significant distortional forces by the wearer's body movements. These forces can tend to compress the napkin laterally, causing it to rope or twist and thereby present a smaller area for fluid pick-up. Although this problem has been addressed in the art, there remains a need for new product designs that will successfully alleviate such distortion problems but that are also easily manufactured so that cost-effective products can be offered to consumers.

[0005] A number of patents have published disclosing sanitary napkins having an absorbent batt folded in a particular configuration.

[0006] U.K. Patent Application GB 2,124,499A discloses a sanitary napkin with an absorbent batt folded along the longitudinal edges to provide a cavity in the bottom portion of the napkin.

[0007] U.S. 3,699,966 to Chapuis discloses a sanitary napkin comprising alternate layers of hydrophilic and hydrophobic material, with the edges of the

hydrophilic material folded inward to define a channel extending through the middle of one side of the napkin.

[0008] Other patents disclosing napkins containing an absorbent batt folded in a "C-fold" configuration are U.S. 3,667,468 to Nystrand et al., U.S. 3,954,107 to Chesky et al., and U.S. 3,364,931 to Hirsch.

[0009] The above-mentioned need for new product designs is achieved by the characterizing portion of claims 1, 11 and 12. Accordingly, this invention relates to an absorbent product for use in a wearer's garment, such as a sanitary napkin, comprising

a body-facing, fluid-pervious cover,
a garment-facing, fluid-impervious backing, and
an absorbent batt therebetween, said absorbent batt being folded upon itself along a pair of generally parallel longitudinal fold lines to form a middle panel and two side panels said middle and two side panels being substantially equivalent in width at the central transverse axis of said absorbent batt. The middle panel is preferably positioned on the body-facing side of the absorbent batt.

[0010] In preferred embodiments, one or more panels of the absorbent batt are pattern-embossed to effect fluid acquisition, holding and transport in the product. For example, in one preferred embodiment, the body-facing panel is provided with a plurality of lengthwise channels and one of the side panels is provided with a plurality of widthwise channels, such channels serving to wick fluid away from the center of the absorbent batt.

[0011] The absorbent product of the invention offers numerous advantages. The folds at the side edges of the absorbent core provide the tri-folded absorbent batt with an inherent mechanical bending resistance which, in turn, gives the batt an enhanced ability to provide a springy force to resist deformation, collapsing or roping.

Brief Description of the Drawings

[0012]

Figure 1 is a top view of an absorbent batt of this invention, prior to being folded.

Figures 2 and 3 are cross-sections of tri-folded absorbent batts utilized in this invention.

Figure 4 is a cross-section of a sanitary napkin incorporating the tri-folded absorbent batt.

Figures 5, 6, 7, 8, and 9 are top views of various absorbent batts of this invention, both prior (a) and after (b) folding.

Detailed Description of the Invention

[0013] The absorbent batt utilized in this invention is illustrated in the Figures 1 - 3 and 5 - 9. Absorbent batt 10 comprises three panels, 11, 12 and 13. Side panel 11 is defined by longitudinal edge 14 and by longitudinal

fold line 15. Middle panel 12 is defined by longitudinal fold line 15 and by longitudinal fold line 16. Side panel 13 is defined by longitudinal fold line 16 and by longitudinal edge 17. The transverse ends of each of the three panels are defined by transverse edges 18 and 19. Dotted line 24 represents the central, transverse axis of the absorbent batt, an axis located midway between transverse edges 18 and 19.

[0014] Fold lines 15 and 16 are generally parallel to one another and are positioned so that each of panels 11, 12 and 13 are substantially equivalent in width at the central transverse axis of the absorbent batt. When panels 11 and 12 are folded at fold lines 15 and 16, the absorbent batt is not in a traditional C-fold configuration. Rather, there is a substantial overlap of side panel 11 and middle panel 12. By substantial overlap it is meant that side panel 11 is folded over middle panel 12 so that longitudinal edge 14 approaches fold line 16 at central transverse axis 24 while still permitting folding about line 16 as shown in the figures. Similarly, side panel 13 is folded over the opposite face 22 of side panel 11 so that longitudinal edge 17 approaches the fold formed at fold line 15 at the central transverse axis 24.

[0015] As shown in Figure 1, the panels 11, 12 and 13 can be substantially equivalent in width through their entire length. Alternatively, however, as shown in Figures 5, 6, 7, and 8, the three panels may be substantially equivalent in width at the central transverse axis 24, but either side panel 11 or 13 or both can taper to a narrower width as they extend longitudinally from the central transverse axis in a variety of patterns. By altering the shapes of side panels 11 and/or 13, it is possible to provide an absorbent batt that is thicker in the central region, where greater absorbency is required, and thinner at the end regions where less absorbency is required, the thinner end regions contributing to greater comfort for the wearer. For example, as shown in Figures 5, 6, 7 and 8, side panels 11 and 13 may be generally trapezoidal in shape.

[0016] The three panels 11, 12 and 13 may be substantially equivalent in length, as shown in Figure 1, or their lengths may vary. For example, in the embodiments illustrated in Figure 9, each of side panels 11 and 13 is shorter in length than middle panel 12. This configuration, too, provides for a pad that is thicker in the central region than at the longitudinal ends, providing both increased comfort and increased absorbency where needed.

[0017] The absorbent batt is preferably formed from both absorbent pulp fibers and resilient, synthetic fibers. The pulp fibers are generally formed from fiberizing wood pulp sheets and generally comprise a combination of long and short fibers. Suitable resilient, synthetic fibers include, but are not limited to, polyester and polyethylene fibers. These fibers tend to be "long", i.e., in the range of about 1.59 mm (1/16") to about 12.7 mm (1/2") long. While the pulp fibers imbue the batt with absorbency, the synthetic fibers add to the resiliency of

the batt.

[0018] It is desirable to have a greater proportion of pulp fibers to synthetic fibers in the body-facing panel of the absorbent batt, panel 12, to enhance the ability of that panel to quickly absorb fluid, and a lower proportion of pulp fibers to synthetic fibers in the garment-facing panel of the absorbent batt, panel 13, where rapid fluid pick-up is not as critical but where added resiliency is beneficial.

[0019] The relative quantities of fibers in each panel can range from 100% to 0% pulp to 0% to 100% synthetic fiber. When middle panel 12 is on the body-facing side of the batt, it is desirable to have rapid fluid distribution in that panel, so middle panel may be beneficially formed from 100% pulp. In side panels 11 and 13, where rapid fluid absorption is not as critical, 100% synthetic fiber can be utilized for resiliency. A composite of about 65% pulp and 35% synthetic fiber has been found to provide an absorbent batt with good resiliency.

[0020] The resiliency of the batt can vary greatly with the type and length of the synthetic fibers utilized. Since the length and resiliency of most synthetic fiber decreases after it is heated to above its melt temperature, it is desirable to use a short <1.59 mm (<1/16") synthetic fiber with a low melt temperature in conjunction with a long synthetic fiber with a high melt temperature. The shorter and lower melt fiber is used to bond the pulp and synthetic fibers together and the longer and higher melt fiber can provide the resilient property that is desired. For example, a batt with a composite of 65% pulp, 20% short low melt synthetic fiber and 15% longer high melt synthetic fiber (a total of 35% synthetic fiber) provides an absorbent batt with better resiliency than a standard 65/35 composite.

[0021] The batt may be formed by known techniques in which the fibers, pulp and/or synthetic, are air-laid. To form the most stable batt, the fibers in the batt are preferably bonded to one another. This may be done by heating the batt to a temperature above the melting temperature of the synthetic fibers so those fibers fuse and bond to one another. Alternatively, bonding agents such as different thermo-bonding fibers, hot melt spray adhesives, and bonding powders may be utilized. Specific means that can be used to bond the fibers together include convection ovens, di-electric ovens (radio frequency and microwave), infrared ovens, heated calender rolls, forced hot-air ovens, forced hot air during the panel forming process, and spray hot melt adhesive during the panel forming process.

[0022] The figures illustrate a tri-fold configuration of the absorbent batt. It is believed that the folded edges formed at fold lines 15 and 16 provide the absorbent batt with resistance to bending forces. This gives the batt the ability to provide a springy force to resist deformation, collapsing or "roping" when subjected to lateral crushing forces, such as those provided to the lateral edges of a sanitary napkin by movement of the wearer's thighs.

[0023] Any one of, or all of, panels 11, 12 and 13 may be provided with embossing to enhance fluid distribution, comfort and/or aesthetics. Such embossing patterns can include, but are not limited to, lengthwise or widthwise channels, diagonal channels, and pockets of embossing.

[0024] In one embodiment illustrated in Figure 1, middle panel 12 has a plurality of longitudinal channels 20 formed therein, and side panel 11 has a plurality of widthwise channels 21 formed therein. In another embodiment, illustrated in figure 5, side panel 13 has a plurality of longitudinal channels and middle panel 12 has a plurality of widthwise channels. Figure 7 shows side panel 13 having a plurality of longitudinal channels and middle panel 12 having a plurality of diagonal channels. The channels provided in the various panels of the absorbent batt serve to wick fluid to all portions of the absorbent batt.

[0025] In the embodiment illustrated in Figure 6, side panel 11 is provided with longitudinal channels and middle panel 12 has been embossed to provide a plurality of raised circular areas 40 on the panel. The raised circular areas provide a feeling of loft and softness, and the indentations around those areas provide a reservoir for acquisition of fluid.

[0026] The embossing patterns provided on the absorbent panels may be provided by means known in the art, for example, by a patterned calender roll, which may or may not be heated. The pitch/pattern for the channel embossing can vary within each respective tooling roll and vary from one pattern to another. An embossing station may be designed to house an upper and lower calender roll which can be set up in a male to female orientation or male to a solid anvil. The rolls can be heated or maintained at ambient temperature depending on the composition of the batt and the desired "set" that is required for specific products. In general, a permanent set can be made on a batt with pulp content of between 65% to 100% without the use of heat. A small amount of moisture, 0.5% to 5% of the weight of the batt, can be added to the batt containing a percentage of pull to obtain a stronger and more permanent set. Batts with a lower percentage of pulp may require heat to obtain a permanent set.

[0027] The pulp pad can be processed through the embossing station with the depth of embossing determined by the pulp thickness and composition. For example, the specification for longitudinal or latitudinal rolls might be as follows: Rolls 25.4 mm - 50.8 mm (1" - 2") wide with varying channel pattern of 3.18 mm - 12.7 mm (1/8" - 1/2") male, 3.18 mm - 12.7 mm (1/8" - 1/2") female with a depth of 3.18 mm to 6.35 mm (1/8" to 1/4"), angle of 60° to 90°. Preferably, the densified channels or areas are at least 6.35 mm (1/4") from the edges and ends of the panel.

[0028] Preferably, the panels of the tri-folded absorbent batt are bonded to one another to help retain the tri-folded configuration. This may be done by appli-

cation of areas of construction adhesive 23, as illustrated in Figure 2. Alternatively, the tri-folded panel may be subjected to heat and/or calendaring to effect bonding of the panels through bonding of the thermoplastic fibers therein, as illustrated in Figure 3.

[0029] Additional fibrous or particulate agents may be incorporated into the fibrous batt. For example, it may be desirable to incorporate superabsorbent particles or fibers in the batt to enhance the absorbency of the batt. Such superabsorbents are well known in the art. One type of superabsorbent material provides particles or fibers which may be described chemically as having a backbone of natural or synthetic polymers with hydrophilic groups or polymers containing hydrophilic groups being chemically bonded to the backbone or an intimate mixture therewith. Included in this class of materials are such modified natural and regenerated polymers as polysaccharides including, for example, cellulose and starch and regenerated cellulose which are modified by being carboxylalkylated, phosphonoalkylated, sulfoalkylated, or phosphorylated to render them highly hydrophilic. Such modified polymers may also be cross-linked to improve their water-insolubility.

[0030] It may also be desirable to incorporate odor control agents in the batt, such as but not limited to, baking soda and activated charcoal.

[0031] Rather than incorporating superabsorbent or odor control agents within the batt itself, these materials may be placed or layered between the panels of the tri-folded batt. For example, baking soda powder or fibrous or particulate superabsorbent may be placed on the surface of the absorbent batt prior to folding, so that it is positioned between the layered panels in the final configuration of the batt. As another example, a panel of superabsorbent material, for example a superabsorbent/tissue laminate or a panel of processed peat moss, either of which may be represented by insert 30 as shown on Figure 4, may be placed between panels of the tri-folded batt

[0032] As illustrated in the figures, each of the three panels in the absorbent batt is generally uniform in thickness. However, the thickness of the panels can vary to provide different profiles. For example, it may be desired to have extra thickness in the center of the napkin, so the thickness of one or more of the panels could be greater in the center than at either or both the transverse or longitudinal edges.

[0033] The dimensions of the absorbent batt are not critical and can be varied according to the type of absorbent product desired. Generally, for a full protection sanitary napkin, the absorbent batt might be in the range of about 209.2 mm (8") in length and about 177.8 mm (7") in width, before tri-folding.

[0034] A sanitary napkin incorporating the tri-folded absorbent batt described above is illustrated in Figure 4. The absorbent batt is contained within a top body-facing, fluid-pervious cover 31 and a bottom, garment-facing, fluid-impervious backing 32. Adhesive means 34

serve to securely adhere the napkin to the wearer's undergarment. The attachment means may comprise adhesive lines covered with release strips 35 which, when peeled from the adhesive strips, leave the adhesive tacky. Alternatively, the attachment means may comprise pressure-sensitive adhesive tape, said tape having a first face permanently adhered to the liquid impermeable cover 32 and an opposite second face adapted to be temporarily attached to the wearer's garment.

[0035] The absorbent batt is preferably placed in the napkin so that middle panel 12, having longitudinal channels, is the body-facing side of the batt and so that side panel 11, having widthwise channels, is the middle portion of the batt.

[0036] The fluid-pervious cover 31 facing provided on the absorbent structure of the present invention should be a film or fabric having a high degree of moisture permeability. For example, the fabric may be polyester, polyethylene, polypropylene, bicomponent fiber, nylon, rayon; or the like. The most suitable fabrics have unusually high elongation, loft, softness and drape characteristics. Films which are perforated or noncontinuous are also satisfactory. Though the cover is moisture permeable, it is preferably of the type which after permeation of the moisture, prevents strike-back of the body fluid when the absorbent structure is approaching saturation.

[0037] The fluid-impervious backing 32 may be a liquid-impermeable polyolefin film, e.g., polyethylene or polyethylene terephthalate.

Claims

1. An absorbent product for use in a wearer's garment, comprising

a body-facing, fluid-pervious cover (31),
a garment-facing, fluid-impervious backing (32),
an absorbent batt (10) therebetween, said absorbent batt being folded upon itself along a pair of generally parallel longitudinal fold lines (15, 16) to form a middle panel (12) and two side panels (11, 13), said three panels (11, 12, 13) being substantially equivalent in width at the central transverse axis (24) of said absorbent batt (10);

wherein said middle panel (12) is on the body-facing side of said absorbent batt (10), and characterized in that

said absorbent batt (10) comprises wood pulp fibers and synthetic fibers such that the proportion of wood pulp fibers to synthetic fibers is greater in said middle, body-facing panel (12) of said absorbent batt (10) than in said side panels (11, 13), and a lower proportion of pulp fibers to synthetic fibers in the garment-facing

panel (13) of the absorbent batt.

2. An absorbent product of Claim 1 which is a sanitary napkin.
3. An absorbent product of Claim 1 wherein said middle body-facing panel (12) is bonded to a first side panel (11) and said first side panel (11) is bonded to a second side panel (13).
4. An absorbent product of Claim 1 wherein superabsorbent material (30) is placed between said middle body-facing panel (12) and one of said side panels (11, 13) of said absorbent batt (10).
5. An absorbent product of Claim 1 wherein odor-controlling material (23) is placed between said middle body-facing panel (12) and one of said side panels (11, 13) of said absorbent batt (10).
6. An absorbent product of Claim 1 wherein said side panels (11, 13) of said absorbent batt (10) are narrower in width at their transverse ends than at the central transverse axis (24) of the absorbent batt (10).
7. An absorbent product of Claim 6 wherein said side panels (11, 13) are generally trapezoidal in shape.
8. An absorbent product of Claim 1 wherein at least one of said side panels (11, 13) is shorter in length than said middle, body-facing panel (12).
9. An absorbent product of Claim 1 wherein one or more panels (11, 12, 13) of said absorbent batt (10) is pattern-embossed.
10. An absorbent product of Claim 9 wherein said pattern is selected from the group consisting of longitudinal channels (20), latitudinal channels (21), diagonal channels and raised dots (40).
11. An absorbent product for use in a wearer's garment comprising

a body-facing, fluid-pervious cover (31),
a garment-facing, fluid-impervious backing (32),
a tri-folded absorbent batt (10) therebetween, wherein said absorbent batt comprises

a first panel (11) defined by a first longitudinal edge (14) of said batt (10) and a first longitudinal fold line (15), said first panel (11) having a plurality of widthwise channels (21),
a second panel (12) defined by said first longitudinal fold line (15) and a second lon-

itudinal fold line (16), said second panel (12) having a plurality of lengthwise channels (20),

a third panel (13) defined by said second longitudinal fold line (16) and a second longitudinal edge (17) of said batt (10),

and wherein said first panel (11) is folded over one face of said second panel (12) at said first fold line (15) so there is a substantial overlap of said first and second panels (11, 12), and where said third panel (13) is folded over said first panel (11) at said second fold line (16); said second panel (12) thereby is on the body-facing side of said absorbent batt (10);

characterized in that

said absorbent batt (10) comprises wood pulp fibers and synthetic fibers such that the proportion of wood pulp fibers to synthetic fibers is greater in said second body-facing panel of said absorbent batt (10) than in said first and third panels (11, 13), and a lower proportion of pulp fibers to synthetic fibers in the garment-facing panel (13) of the absorbent batt.

12. An absorbent core for use in an absorbent product suitable for placement in a wearer's garment comprising an absorbent batt (10) folded upon itself along a pair of generally parallel longitudinal fold lines (15, 16) to form a middle panel (12) and two side panels (11, 13), said three panels being substantially equivalent in width at the central transverse axis (24) of said absorbent batt (10);

characterized in that

said absorbent batt (10) comprises wood pulp fibers and synthetic fibers such that the proportion of wood pulp fibers to synthetic fibers is greater in said middle panel of said absorbent batt (10) than in said side panels (11, 13), and a lower proportion of pulp fibers to synthetic fibers in the garment-facing panel (13) of the absorbent batt.

13. An absorbent core of Claim 12 wherein said middle panel (12) is bonded to one of said side panels (11, 13) and said side panel (11) is bonded to said other side panel (13).

14. An absorbent core of Claim 12 wherein superabsorbent material (30) is placed between said middle panel (12) and one of said side panels (11, 13) of said absorbent batt (10).

15. An absorbent core of Claim 12 wherein odor-controlling material (23) is placed between said middle panel (12) and one of said side panels (11, 13) of said absorbent batt (10).

16. An absorbent core of Claim 12 wherein said side

panels (11, 13) of said absorbent batt (10) are narrower in width at their transverse ends than at the central transverse axis (24) of the absorbent batt.

17. An absorbent core of Claim 16 wherein said side panels (11, 13) are generally trapezoidal in shape.

18. An absorbent core of Claim 12 wherein at least one of said side panels (11, 13) is shorter in length than said middle panel (12).

19. An absorbent core of Claim 12 wherein one or more panels (11, 12, 13) of said absorbent batt (10) is pattern-embossed.

20. An absorbent product of Claim 19 wherein said patterns are selected from the group consisting of longitudinal channels (20), latitudinal channels (21), diagonal channels and raised dots (40).

Patentansprüche

1. Absorbierendes Produkt zur Verwendung in einem Kleidungsstück einer Trägerin, mit folgenden Merkmalen:

eine dem Körper zugewandte, fluiddurchlässige Abdeckung (31);

eine dem Kleidungsstück zugewandte, fluidundurchlässige Unterlage (32);

ein absorbierender Wickel (10) zwischen diesen, wobei der absorbierende Wickel entlang zwei im wesentlichen parallelen, in Längsrichtung verlaufenden Falzlinien (15, 16) auf sich selbst gefaltet ist, um eine mittlere Bahn (12) und zwei Seitenbahnen (11, 13) zu bilden, wobei die drei Bahnen (11, 12, 13) bei der mittleren Querachse (24) des absorbierenden Wickels (10) im wesentlichen die gleiche Breite haben;

wobei die mittlere Bahn (12) auf der dem Körper zugewandten Seite des absorbierenden Wickels (10) liegt,

dadurch gekennzeichnet, daß

der absorbierende Wickel (10) Zellstoffasern und synthetische Fasern aufweist, wobei das Verhältnis der Zellstoffasern zu den synthetischen Fasern in der mittleren, dem Körper zugewandten Bahn (12) des absorbierenden Wickels (10) höher ist als in den Seitenbahnen (11, 13) und das Verhältnis der Zellstoffasern zu den synthetischen Fasern in der dem Kleidungsstück zugewandten Bahn (13) des absorbierenden Wickels niedriger ist.

2. Absorbierendes Produkt nach Anspruch 1, dadurch gekennzeichnet, daß es eine Damenbinde ist.

3. Absorbierendes Produkt nach Anspruch 1, bei dem die mittlere, dem Körper zugewandte Bahn (12) mit der ersten Seitenbahn (11) verbunden ist und die erste Seitenbahn (11) mit einer zweiten Seitenbahn (13) verbunden ist. 5
4. Absorbierendes Produkt nach Anspruch 1, bei dem ein hochabsorbierendes Material (30) zwischen die mittlere, dem Körper zugewandte Bahn (12) und eine der Seitenbahnen (11, 13) des absorbierenden Wickels (10) gelegt ist. 10
5. Absorbierendes Produkt nach Anspruch 1, bei dem ein Geruchskontrollmaterial (32) zwischen die mittlere, dem Körper zugewandte Bahn (12) und eine der Seitenbahnen (11, 13) des absorbierenden Wickels (10) gelegt ist. 15
6. Absorbierendes Produkt nach Anspruch 1, bei dem die Seitenbahnen (11, 13) des absorbierenden Wickels an ihren Querenden eine geringere Breite haben als bei der mittleren Querachse (24) des absorbierenden Wickels (10). 20
7. Absorbierendes Produkt nach Anspruch 6, bei dem die Seitenbahnen (11, 13) im wesentlichen trapezoidförmig sind. 25
8. Absorbierendes Produkt nach Anspruch 1, bei dem wenigstens eine der Seitenbahnen (11, 13) in Längsrichtung kürzer ist als die mittlere, dem Körper zugewandte Bahn (12). 30
9. Absorbierendes Produkt nach Anspruch 1, bei dem eine oder mehrere Bahnen (11, 12, 13) des absorbierenden Wickels (10) eine geprägte Struktur aufweisen. 35
10. Absorbierendes Produkt nach Anspruch 9, bei dem die Struktur aus der Gruppe ausgewählt ist, die Längskanäle (20), Querkannäle (21), Diagonalkanäle und erhabene Punkte (40) umfaßt. 40
11. Absorbierendes Produkt zur Verwendung in einem Kleidungsstück einer Trägerin, mit folgenden Merkmalen: 45
 - eine dem Körper zugewandte, fluiddurchlässige Abdeckung (31);
 - eine dem Kleidungsstück zugewandte, fluidundurchlässige Unterlage (32);
 - ein dreifach gefalteter, absorbierender Wickel (10) zwischen diesen, wobei der absorbierende Wickel folgende Merkmale aufweist: 50
 - eine erste Bahn (11), die von einer ersten Längskante (14) des Wickels (10) und einer ersten in Längsrichtung verlaufenden Falzlinie (15) eingegrenzt ist, wobei die erste Bahn (11) mehrere in Richtung ihrer Breite verlaufende Kanäle (21) aufweist, ein zweites Feld (12), das von der ersten in Längsrichtung verlaufenden Falzlinie (15) und einer zweiten in Längsrichtung verlaufenden Falzlinie (16) eingegrenzt ist, wobei das zweite Feld (12) mehrere in Längsrichtung verlaufende Kanäle (20) aufweist, ein drittes Feld (13), das durch die zweite in Längsrichtung verlaufende Falzlinie (16) und eine zweite Längskante (17) des Wickels (10) eingegrenzt ist, 55
12. Absorbierender Kern zur Verwendung in einem absorbierenden Produkt, das in einem Kleidungsstück einer Trägerin getragen werden kann, mit einem absorbierenden Wickel (10), der entlang zwei im wesentlichen parallelen, in Längsrichtung verlaufenden Falzlinien (15, 16) auf sich selbst gefaltet ist, um eine mittlere Bahn (12) und zwei Seitenbahnen (11, 13) zu bilden, wobei die drei Bahnen bei der mittleren Querachse (24) des absorbierenden Wickels (10) im wesentlichen die gleiche Breite haben; 60
 - dadurch gekennzeichnet, daß
 - der absorbierende Wickel (10) Zellstoffasern und synthetische Fasern aufweist, wobei das Verhältnis der Zellstoffasern zu den synthetischen Fasern in der mittleren, dem Körper zugewandten Bahn (12) des absorbierenden Wickels (10) höher ist als in den Seitenbahnen (11, 13) und das Verhältnis der Zellstoffasern zu den synthetischen Fasern in der dem Kleidungsstück zugewandten Bahn (13) des absorbierenden Wickels niedriger ist. 65
13. Absorbierendes Produkt nach Anspruch 12, bei

dem die mittlere Bahn (12) mit einer der Seitenbahnen (11, 13) verbunden ist und diese Seitenbahn (11) mit der anderen Seitenbahn (13) verbunden ist.

14. Absorbierendes Produkt nach Anspruch 12, bei dem ein hochabsorbierendes Material (30) zwischen die mittlere Bahn (12) und eine der Seitenbahnen (11, 13) des absorbierenden Wickels (10) gelegt ist.
15. Absorbierendes Produkt nach Anspruch 12, bei dem ein Geruchskontrollmaterial (32) zwischen die mittlere Bahn (12) und eine der Seitenbahnen (11, 13) des absorbierenden Wickels (10) gelegt ist.
16. Absorbierendes Produkt nach Anspruch 12, bei dem die Seitenbahnen (11, 13) des absorbierenden Wickels an ihren Querenden eine geringere Breite haben als bei der mittleren Querachse (24) des absorbierenden Wickels (10).
17. Absorbierendes Produkt nach Anspruch 17, bei dem die Seitenbahnen (11, 13) im wesentlichen trapezoidförmig sind.
18. Absorbierendes Produkt nach Anspruch 12, bei dem wenigstens eine der Seitenbahnen (11, 13) in Längsrichtung kürzer ist als die mittlere Bahn (12).
19. Absorbierendes Produkt nach Anspruch 12, bei dem eine oder mehrere Bahnen (11, 12, 13) des absorbierenden Wickels (10) eine geprägte Struktur aufweisen.
20. Absorbierendes Produkt nach Anspruch 9, bei dem die Struktur aus der Gruppe ausgewählt ist, die Längskanäle (20), Querkannäle (21), Diagonalkanäle und erhabene Punkte (40) umfaßt.

Revendications

1. Produit absorbant destiné à être utilisé sur un vêtement d'une utilisatrice, comprenant :

un côté de dessus faisant face au corps et perméable aux fluides (31),
un côté de dessous faisant face aux vêtements et imperméable aux fluides (32),
un molleton absorbant (10) entre ces deux côtés, ledit molleton absorbant étant replié sur lui-même le long d'une paire de lignes de pliage longitudinales généralement parallèles (15, 16) afin de former un panneau médian (12) et deux panneaux latéraux (11, 13), lesdits trois panneaux (11, 12, 13) ayant une largeur substantiellement équivalente au niveau de l'axe central transversal (24) dudit molleton

absorbant (10) ;

dans lequel ledit panneau médian (12) est placé sur le côté faisant face au corps dudit molleton absorbant (10), et
caractérisé en ce que

ledit molleton absorbant (10) comprend des fibres de pulpe de bois et des fibres synthétiques de telle sorte que la proportion de fibres de pulpe de bois par rapport à la proportion de fibres synthétiques soit plus importante dans ledit panneau médian faisant face au corps (12) dudit molleton absorbant (10) que dans lesdits panneaux latéraux (11, 13), et de telle sorte que la proportion de fibres de pulpe par rapport aux fibres synthétiques soit moins importante dans le panneau faisant face aux vêtements (13) du molleton absorbant.

2. Produit absorbant selon la revendication 1, qui est une serviette hygiénique.
3. Produit absorbant selon la revendication 1, dans lequel ledit panneau médian faisant face au corps (12) est lié à un premier panneau latéral (11) et ledit premier panneau latéral (11) est lié à un second panneau latéral (13).
4. Produit absorbant selon la Revendication 1, dans lequel le matériau superabsorbant (30) est placé entre ledit panneau médian faisant face au corps (12) et l'un desdits panneaux latéraux (11, 13) dudit molleton absorbant (10).
5. Produit absorbant selon la Revendication 1, dans lequel du matériau de contrôle des odeurs (23) est placé entre ledit panneau médian faisant face au corps (12) et l'un desdits panneaux latéraux (11, 13) dudit molleton absorbant (10).
6. Produit absorbant selon la Revendication 1, dans lequel lesdits panneaux latéraux (11, 13) dudit molleton absorbant (10) sont plus étroits en largeur au niveau de leurs extrémités transversales qu'au niveau de l'axe transversal central (24) du molleton absorbant (10).
7. Produit absorbant selon la Revendication 6, dans lequel lesdits panneaux latéraux (11, 13) ont une forme généralement trapézoïdale.
8. Produit absorbant selon la Revendication 1, dans lequel au moins l'un desdits panneaux latéraux (11, 13) est plus court en longueur que ledit panneau médian faisant face au corps (12).
9. Produit absorbant selon la revendication 1, dans lequel un ou plusieurs panneaux (11, 12, 13) dudit molleton absorbant (10) est muni de motifs gaufrés.

10. Produit absorbant selon la Revendication 9, dans lequel lesdits motifs sont sélectionnés à partir du groupe composé de canaux s'étendant dans le sens de la longueur (20), de canaux s'étendant dans le sens de la largeur (21), de canaux s'étendant dans le sens diagonal et de points surélevés (40).

11. Produit absorbant destiné à être utilisé sur un vêtement d'un utilisateur comprenant

un côté de dessus faisant face au corps et perméable aux fluides (31),
un côté de dessous faisant face aux vêtements et imperméable aux fluides (32),
un molleton absorbant (10) entre ces deux côtés, dans lequel ledit molleton absorbant comprend

un premier panneau (11) défini par un premier bord longitudinal (14) dudit molleton (10) et une première ligne de pliage longitudinale (15), ledit premier panneau (11) étant muni d'une pluralité de canaux s'étendant dans le sens de la largeur (21),
un second panneau (12) défini par ladite première ligne de pliage longitudinale (15) et par une seconde ligne de pliage longitudinale (16), ledit second panneau étant muni d'une pluralité de canaux s'étendant dans le sens de la longueur (20),
un troisième panneau (13) défini par ladite seconde ligne de pliage longitudinale (16) et un second bord longitudinal (17) dudit molleton,

et dans lequel ledit premier panneau (11) est replié sur une face dudit second panneau (12) au niveau de ladite première ligne de pliage (15) de telle sorte qu'il y ait un chevauchement substantiel entre lesdits premier et second panneaux (11, 12), et dans lequel ledit troisième panneau (13) est replié sur ledit premier panneau (11) au niveau de ladite seconde ligne de pliage (16) ; ledit second panneau étant ainsi placé sur le côté faisant face au corps dudit molleton absorbant (10) ;

caractérisé en ce que

ledit molleton absorbant (10) comprend des fibres de pulpe de bois un côté de dessus faisant face au corps et perméable aux fluides (31),

un côté de dessous faisant face aux vêtements et imperméable aux fluides (32), un molleton absorbant (10) entre ces deux côtés, ledit molleton absorbant étant composé de fibres synthétiques de telle sorte que la proportion de fibres de pulpe de bois par rapport aux fibres

synthétiques soit plus importante dans ledit panneau faisant face au corps dudit molleton absorbant (10) que dans lesdits premier et troisième panneaux (11, 13), et que la proportion de fibres de pulpe par rapport aux fibres synthétiques soit plus faible dans le panneau faisant face aux vêtements (13) du molleton absorbant.

12. Partie centrale absorbante destinée à être utilisée dans un produit absorbant approprié pour être placé sur les vêtements d'un utilisateur, comprenant un molleton absorbant (10) replié sur lui-même le long d'une paire de lignes de pliage longitudinales généralement parallèles (15, 16) afin de former un panneau médian (12) et deux panneaux latéraux (11, 13), lesdits trois panneaux ayant une largeur substantiellement équivalente au niveau de l'axe transversal central (24) dudit molleton absorbant (10) ;

caractérisé en ce que

ledit molleton absorbant (10) comprend des fibres de pulpe de bois et des fibres synthétiques, de telle sorte que la proportion de fibres de pulpe de bois par rapport à celle de fibres synthétiques soit plus importante dans ledit panneau médian dudit molleton absorbant (10) que dans lesdits panneaux latéraux (11, 12) et que la proportion de fibres de pulpe par rapport aux fibres synthétiques soit plus faible dans le panneau faisant face aux vêtements (13) du molleton absorbant.

13. Partie centrale absorbante selon la Revendication 12, dans laquelle ledit panneau médian (12) est lié à l'un desdits panneaux latéraux (11, 13) et ledit panneau latéral (11) est lié audit autre panneau latéral (13).

14. Partie centrale absorbante selon la Revendication 12, dans laquelle du matériau superabsorbant (30) est placé entre ledit panneau médian (12) et l'un desdits panneaux latéraux (11, 13) dudit molleton absorbant (10).

15. Partie centrale absorbante selon la Revendication 12, dans laquelle un matériau de contrôle des odeurs (23) est placé entre ledit panneau médian (12) et l'un desdits panneaux latéraux (11, 13) dudit molleton absorbant (10).

16. Partie absorbante selon la Revendication 12, dans laquelle lesdits panneaux latéraux (11, 13) dudit molleton absorbant (10) sont plus étroits en largeur au niveau de leurs extrémités transversales qu'au niveau de l'axe central transversal (24) du molleton absorbant.

17. Partie centrale absorbante selon la Revendication

16, dans laquelle lesdits panneaux latéraux (11, 13) ont une forme généralement trapézoïdale.

18. Partie centrale absorbante selon la Revendication 12, dans laquelle au moins l'un desdits panneaux latéraux (11, 13) est plus court que ledit panneau médian (12). 5
19. Partie centrale absorbante selon la Revendication 12, dans laquelle un ou plusieurs panneaux (11, 12, 13) dudit molleton absorbant (10) est (sont) muni(s) de motifs gaufrés. 10
20. Produit absorbant selon la Revendication 19, dans lequel lesdits motifs sont sélectionnés à partir du groupe composé de canaux s'étendant dans le sens de la longueur (20), de canaux s'étendant dans le sens de la largeur (21), de canaux s'étendant en diagonale et de points en relief (40). 15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5a




FIG. 5b




FIG. 6a




FIG. 6b




FIG. 7a




FIG. 7b




FIG. 8a




FIG. 8b




FIG. 9a




FIG. 9b